

EV-Flex Lite™

EV charging station **Level 2**

Meet the best-in-class EV charging network technology for at home. The EV-Flex Lite™ Level 2 charging station is the ideal EV charging solution for single family residential or light commercial properties.

Sleek, compact modern design

Flexibly mounted on a wall, ceiling, pole or pedestal

Smartphone App user authentication

Real-time load management and demand response

Tamper resistant; rated for indoor/outdoor use

Universal compatibility

Real-time load management and demand response



EV-Flex Lite™ Specifications

Electrical	<ul style="list-style-type: none"> • 32 A / 768 kW max output, 60 Hz • 40 A / 9.6 kW max output, 60 Hz (optional upgrade) • 208/240 VAC, single phase input • Hardwired, single port 		
Connector	<ul style="list-style-type: none"> • 25 ft. charging cable (18 ft. optional) • SAE J1772 Type 1 standard compliant 		
Network Connectivity	<ul style="list-style-type: none"> • Built-in Wi-Fi (802.11 b/g/n) • OCPP 1.6 Communication Protocol 		
Firmware	<ul style="list-style-type: none"> • 90-day, 15-minute encrypted interval data storage • Persistent data storage upon power interruption • Over the Air (OTA) updates available via Loop Network™ 		
Core Specifications	<ul style="list-style-type: none"> • Weatherproof, dust-tight: NEMA 4 (IP66), IK10 tamper resistant • Integrated cable management saddle and holster • Operating Temperature = -30 to 50 °C / -22 to 122 °F • Metering Accuracy= Embedded < ± 1% • User Interface = Configurable OLED display • Status Indicators = Power/Ready, Charging, Fault • Wall, ceiling, pole or pedestal mounting options • Main Enclosure Dimensions = 11.14" H x 7.56" W x 3.11" D • Weight = 5.28 kg / 11.64 lbs • User access control through QR code or Smartphone • Built-in load management (NEC 625.42 compliant, UL 60730 recognized) 		
Certifications + Standards	<ul style="list-style-type: none"> • UL, FCC, Energy Star • Open ADR 2.0b compliant • CTEP, NTEP 		
Loop Network™ (Optional)	<ul style="list-style-type: none"> • Web-based Charger Management System (CMS) • Mobile app (iOS/Android) for drivers • Public or private network enabled • Flexible network billing models (Pay Per Use, Fixed, Hybrid) • Automated billing & real-time payment resolution 		
Warranty	<ul style="list-style-type: none"> • 3-year limited product warranty (parts only) • 5-year and 10-year extended warranties available 		
Ordering	<table> <tr> <td>EV-Flex Lite™ (768 kW) Single Port Charger #EVS-32A-L2-002</td><td>EV-Flex Lite™ (9.6 kW) Single Port Charger #EVS-40A-L2-002</td></tr> </table>	EV-Flex Lite™ (768 kW) Single Port Charger #EVS-32A-L2-002	EV-Flex Lite™ (9.6 kW) Single Port Charger #EVS-40A-L2-002
EV-Flex Lite™ (768 kW) Single Port Charger #EVS-32A-L2-002	EV-Flex Lite™ (9.6 kW) Single Port Charger #EVS-40A-L2-002		

